Approved Doors and Windows for Manufactured Homes

The following items have been approved by the Minnesota Department of Labor and Industry (DLI) for use in HUD code manufactured homes.

Doors

- 1. 5140 Series STANDARD SIZES
 - 30" x 76"
 - 30" x 78"
 - 32" x 72"
 - 32" x 76"
 - 32" x 78"
 - 34" x 76"
 - 34" x 80"
 - 36" x 80"
 - 38" x 82"
- 2. CAMBERED DOOR Exterior
 - Door is pre-cambered at manufacturer for consistency.
 - Door does not require adjustment of camber at installation.
 - Door will "spring" to fit flat or convex walls.
 - Door is weather tight.
 - 1/8" to 3/16" Camber 1/8" to 3/16" Camber
- 3. 5210 Series AVAILABLE STORM DOOR STYLES STANDARD SIZES
 - 34" x 76"
 - 34" x 80"
 - 38" x 80"
- 4. 5600/5900 Series STANDARD SIZES
 - 38" x 76"
 - 38" x 80"
 - 38" x 82"
 - 32" x 76"
 - 34" x 80"
- 5. Kinro Out-Swing Exterior Door With Vertical Sliding Window #0D3072VS, #0D3272VS, #0D3276VS, #0D3476VS
 - 34" x 76"
 - 32" x 72"
 - 32" x 76"
 - 30" x 72"
- 6. Any other style or series requires approval from DLI.

Approved Doors and Windows for Manufactured Homes

Windows

1. Kinro

	1500 SINGLE H	1500 SINGLE HUNG	
	Minimum	Maximum	
Rough Opening Width	14.50"	46.50"	
Rough Opening Height	27.25"	68.38"	
Color Options	White, Tan	·	

1500 PICTURE	
Minimum	Maximum
14.5"	62.50"
10.25"	68.38"
White, Tan	

	1500 XO/OX HORIZONTAL SLIDER	
	Minimum	Maximum
Rough Opening Width	24.50"	72.50"
Rough Opening Height	10.25"	58.88"
Color Options	White, Tan	

1500 XOX DOUBLE END SLIDER		
Minimum	Maximum	
72.50"	94.50"	
30.25" 58.88"		
White, Tan		

	9750 SINGLE HUNG	
	Minimum	Maximum
Rough Opening Width	14.25"	46.50"
Rough Opening Height	27.25"	72.25"
Color Options	White, Clay	

9770 DOUBLE HUNG		
Minimum Maximum		
14.25"	46.50"	
27.25"	72.25"	
White, Clay		

9700 PICTURE	
Minimum	Maximum
14.25"	93.25"
8.25"	72.25"
White, Clay	

	9990 XO/OX HORIZONTAL SLIDER	
	Minimum	Maximum
Rough Opening Width	24.25"	72.25"
Rough Opening Height	12.25"	60.25"
Color Options	White, Clay	

9990XOX DOUBLE END SLIDER			
Minimum Maximum			
46.5" 94.25"			
12.25" 60.25"			
White, Clay			

	18000/18534 SINGLE HUNG	
	Minimum	Maximum
Rough Opening Width	14.25"	36.25"
Rough Opening Height	27.25" 72.25"	
Color Options	White, Mill, Bronze	

18000/18534 PICTURE		
Minimum Maximum		
14.25" 93.25"		
8.25" 72.25"		
White, Mill, Bronze		

	19000/19534 XO/OX HORIZONTAL SLIDER	
	Minimum	Maximum
Rough Opening Width	24.25"	72.25"
Rough Opening Height	12.25"	60.25"
Color Options	White, Mill, Bronze	

18000/18534 VERTICAL SLIDER		
Minimum	Maximum	
14.25"	46.50"	
27.25"	72.25"	
White, Mill, Bronze		

Approved Doors and Windows for Manufactured Homes

	5700 VERTICAL STORM SLIDER	
	Minimum	Maximum
Rough Opening Width	11.44"	45.44"
Rough Opening Height	12.17"	34.67"
Color Options	White, Bronze	
	5800 XO/OX HORIZONTAL SLIDING STORM	
	Minimum	Maximum
Rough Opening Width	24.25"	72.25"
Rough Opening Height	12.25"	60.25"

- 2. Any other style or series must be certified and listed with the American Architectural Manufacturers Association (AAMA) for manufactured homes found
 - at: https://fgiaonline.org/pages/manufactured-housing-certification.